

## Fine white primer coating for interior walls

**RIALTO PRIMER ONE** is a white hiding priming coat based on fine particle of polymer emulsions with high adhesion properties, fine aggregates, titanium dioxide and a broad spectrum anti-mold agents. Its adhesion and binding properties make it the ideal basecoat for application for acrylic paints, acrylic stucco and smooth plasters, particularly over smooth, flat substrates.

### PROPERTIES

- high adhesion capacity
- good water vapor permeability
- not harmful
- permanent fungicide
- good hiding power
- not flammable
- easy to use either by brush or roller
- specific gravity:  $1.55 \pm 0.05$  kg/l
- viscosity at quality control:  
non – Newtonian product
- average value  $> 12.500 \pm 1.000$  mPas
- percentage solids:  $64,00 \pm 2\%$  by weight
- VOC: 25 g/l

### COVERING CAPACITY

The average coverage of **RIALTO PRIMER ONE** when rolled on is approximately 800 - 1,000 sq. ft. when diluted 10%. When sprayed on using a 631 spray tip, coverage is typically 1,000 sq.ft. when diluted 15%. Can be tinted for better product coverage.

### PACKAGING

**RIALTO PRIMER ONE** is available in a 15 liter / 52 lb. container

### COLOR RANGE

**RIALTO PRIMER ONE** is available in any of our 72 standard colors, or we will match any custom color.

### REFERENCES

For further information regarding the product mentioned in the text, see the following technical sheets:

**RIALTO ANTIQUA**  
**RIALTO NLP**  
**RIALTO EPOCA MARMO**  
**RIALTO EPOCA OTTOCENTO**  
**RIALTO EPOCA SPATOLATO**  
**RIALTO SOLUTION**  
**RIALTO EVOLUTION**  
**RIALTO VELASIL**  
**RIALTO VENEZIANO**  
**RIALTO SAPONE SEALER**

### PURPOSES

**RIALTO PRIMER ONE** is suitable for the following applications:

- matte white basecoat for interior walls
- white priming coat for drywall, plasterboards particularly smooth and flat where **RIALTO FINISH** may be too rough for the desired smooth plaster effect
- bonding agent on dusty substrates like gypsum
- bonding agent highly compatible with acrylic paints and decorative acrylic stuccos for interiors
- anti-mold basecoat for application of anti-mold finishing paints in areas prone to growth of fungus

### WORKING INSTRUCTIONS

- surfaces should be cleaned and loose material removed
- apply one coat of **RIALTO PRIMER ONE** (diluted with 10% water) with roller and let dry for at least **12 hours** or you may apply **RIALTO PRIMER ONE** (diluted with 15% water) with a sprayer and let dry for at least **12 hours**
- do not apply **RIALTO PRIMER ONE** to brick with evident signs of efflorescence or dampness
- do not apply if there is a risk of rain within **24 hours**, or when air surface temperatures are below 41°F (5°C)
- protect from frost and temperatures above 86°F (30°C)
- check with your local department of environmental quality for disposal requirements and recycle whenever possible

*Coventry Interiors Location: Rialto Hotel, Vancouver, Canada*



V-1483